



## RESILIENT SEAT VALVE BOLT DATA

### WAFER BF SERIES FLANGE BOLT DATA

WAFER TYPE							
Valve Size	Holes	Thread Description	No.	Standard Stud	Machine Bolt	No.	Short Studs
2	4	5/8"-11 UNC	4	5"	4"	0	-
2.5	4	5/8"-11 UNC	4	5 1/4"	4 1/2"	0	-
3	4	5/8"-11 UNC	4	5 1/2"	4 1/2"	0	-
4	8	5/8" -11 UNC	8	5 3/4"	4 3/4"	0	-
5	8	3/4"-10 UNC	8	6"	5"	0	-
6	8	3/4"-10 UNC	8	6 1/4"	5 1/4"	0	-
8	8	3/4"-10 UNC	8	6 3/4"	5 3/4"	0	-
10	12	7/8"-9 UNC	12	7 1/2"	6"	0	-
12	12	7/8"-9UNC	12	7 3/4"	6 3/4"	0	-
14	12	1"-8 UNC	12	8 1/4"	7"	0	-
16	16	1"-8	16	9 1/2"	8"	0	-
18	16	1 1/8"7 UNC	16	10	8 3/4"	0	-
20	20	1 1/8"-7 UNC	20	11 1/4"	9 3/4"	0	-
24	20	1 1/4"-7 UNC	20	12 3/4"	11 1/4"	0	-
28	28	1 1/4"-7 UNC	24	15"	13 1/2"	8	6 1/2"
30	28	1 1/4"-7 UNC	24	15 1/2"	14"	8	6 1/2"
32	28	1 1/2"-6 UNC	24	17 1/4"	15 1/2"	8	7 1/4"
36	32	1 1/2"-6 UNC	28	18"	16 1/4"	8	7 3/4"
40	36	1 1/2"-6 UNC	32	19	17 1/4"	8	8"
42	36	1 1/2"-6 UNC	32	21"	19 1/4"	8	8 1/4"
48	44	1 1/2"-6 UNC	40	23"	21"	8	8 3/4"

 <small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PRATT INDUSTRIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PRATT INDUSTRIAL IS PROHIBITED.</small>	No.	Revision	Date	Drawn by	Title	File No.	
	0		10-3-14	AC	WAFER BF SERIES FLANGE BOLT DATA	Date of Issue	
					Checked by	DWG No.	Date of Issue
				Approved by	BD-100114-BF1	10-3-14	